

Model	Noise level db(A)	Pump speed		Final pressure (50 Hz), Pa	Final pressure (50 Hz)	Motor power	Voltage		Weight		Leak tightness	Water vapor capacity	Air flushing	Inlet connection	Outlet connection	Cooling system	Ambient temperature	
	(*2)	§	m ³ /h			kW	V		kg		Pa • m ³ /s	g/Tag	L/min	NW	NW		°C	
								Single-phase	Three-phase	Single- phase	Three- phase							
ISP-50	48	50	3,7	20	2.0 *10 ⁻¹	0,1	AC 100 V ; AC 200 V ; AC 230 V		12				3 (with air flushing)	4				
ISP-90	52 (57 with air flushing)	90	5,4	5	5.0 x 10 ⁻²	0,15	100, 115, 200, 230 (with temperature protection)	-	14	-			5 (with air flushing)	9	25	16	Air-cooled	5~40
ISP-250C	58 (66 with air flushing)	250	15	1,6	1.6 x 10 ⁻²	0,4			25	23			25 (with air flushing)	10	25	16	Air-cooled	5~40
ISP-500C	60 (68 with air flushing)	500	30	1	1.0x10 ⁻²	0,6	100, 115, 200, 230 (with temperature protection)	200,208,230,380,450,460	44	38						25		
ISP-1000E	67 (74 with air flushing)	1000	60		1.0 x 10 ⁻²	1,4	-	200,208,230,380,450,460	-	68				25 (with air flushing)	40	40	40	Air-cooled