

# NG CASTORE PRO HP

Membrane Nitrogen generator  
electronic controlled

The NitroGen series CASTORE PRO HP are Membrane Nitrogen Generators. They are engineered to transform standard compressed air into a safe, regulated supply of Nitrogen with a purity greater than 99.5%.

The exclusive electronic flow control allows to generate Nitrogen with a higher purity using a smaller volume of air which results in reduced energy costs and maintenance of any external compressor. Continuous control of the operating parameters allows to maintain the system at its maximum efficiency.

The CASTORE PRO HP has been developed to meet specific requirements in term of gas, flow, purity and pressure for ELSD, TOC, ICP, DSC/TGA and other applications. It can be used for the evaporation of solvents in samples being analysed.

## Main applications

- ELSD
- TOC
- ICP
- DSC/TGA

## Main advantages

- ✓ Nitrogen purity >99.5%
- ✓ Low noise
- ✓ Low maintenance
- ✓ Generates nitrogen on demand
- ✓ Smart energy save mode
- ✓ Exclusive electronic flow control
- ✓ Designed to run 24 hours a day





## Specifications

Models: NG CASTORE PRO HP	4	8
<b>N2 outlet</b>		
Flow rate (Max)	4 l/min	8 l/min
Outlet pressure (min / Max)	2.0 bars / Inlet pressure – 0.5 bar	
Nitrogen purity (Inlet Pressure >= 6 bar)	> 99.5 % @ 4 l/min Dew-point < -40°	> 99.5 % @ 8 l/min Dew-point < -40°
<b>Air inlet</b>		
Air inlet requirement	Particulate: <1 micron	
	Dewpoint: < -20°C (-4°F) not condensing	
	Oil: <0.01 mg/m <sup>3</sup>	
Flow rate Max (@7 Bar)	40 L/min	45 L/min
Supply pressure (min / Max)	5 bars / 10bars	
Temperature (min / Max)	1°C (34°F)45°C(113°F)	
<b>Communication</b>		
LCD with touch screen	Standard	
RS485	Standard	
RS232	For service	
<b>General data</b>		
Supply rating	100-240Vac 47..63Hz	
Connection type	IEC320-C13	
Installation power (max)	25W (30VA)	
Fuse rating (5x20mm)	1A (250Vac – T)	
Net weight	<35 kg	
Dimensions (W x D x H) mm	280 x 320 x 1200	
<b>Connections</b>		
N2 outlet port	¼" BSPP female	
Inlet port	¼" BSPP female	
Drain port	¼" BSPP female	
<b>Operating/storage conditions</b>		
Temperature	5-35°C (41-95°F)	
Humidity (max, non condensing)	80% at 25°C (77°F)	
Noise	<25dB(A)	
IP rating	IP20	
Pollution degree rating	2 (with no aromatic compounds)	
Altitude	< 2000m	

### Ordering codes

#### Gas Generators

6920.50.004 CASTORE PRO HP 4

6920.50.008 CASTORE PRO HP 8

#### Accessories

6920.50.012 O2 sensor option (%)

#### Consumable

6930.00.140 Service Kit 8000H for CASTORE models



**LNI Swissgas**

[www.lni-swissgas.eu](http://www.lni-swissgas.eu)

Registered office: Via Sassoferato 1, 20135 Milano MI  
Logistics centre: Via E. Mattei 9, 35038 Torreglia PD